


Product Features:

- 3528 SMD
- Voltage: AC 100-250V
- Pure Aluminum with transparent , milky or striped plastic cover
- Please remove ballast and starter off before using
- CW: 6000K-7000K NW: 4000K-4500K WW: 2700K-3300K



Patent No.: ZL 2010 2 0281457.1



T8-3528

- suit for magnetic ballast
- can be rotated 120 degree
- workable also at two sides connected



Transparent



Striped



Milky



ITEM TECHNICAL DATA

COLOR	λ d(nm)or Tc(K)	60cm		120cm		150cm
		120SMD Lm / W	150SMD Lm / W	270SMD Lm / W	360SMD Lm / W	450SMD Lm / W
○ White	6000-7000k	680lm/9W	850lm/11.5W	1500lm/21W	2000lm/27W	2400lm/33W
○ Natural light	4000-4500k	680lm/9W	850lm/11.5W	1500lm/21W	2000lm/27W	2400lm/33W
○ Warm white	2700-3300k	680lm/9W	850lm/11.5W	1500lm/21W	2000lm/27W	2400lm/33W

Product size

Series	Dia.[Ø]xH	Single box	Carton	Q.T.Y	Packing weight (G.W)
T8-3528-60cm	26x600mm	615x33mm	630x210x210mm	25pcs	7.6kg
T8-3528-120cm	26x1200mm	1230x33mm	1250x210x210mm	25pcs	14.6kg
T8-3528-150cm	26x1500mm	1510x33mm	1545x210x210mm	25pcs	17.1kg